

## NVAF Axial Fan

### NVAF Axial Fan

Axial fan is produced in different model options between 350 mm - 1250 mm diameter range  
 Usages: general ventilation, stair and elevator pressurization fan systems, fresh air fan, and as an exhaust fans.



MODEL	Air Flow (m3/h)	Motor power (kw)	Static pressure (PA)	Motor Speed (RPM)	Operating voltage (V)	Fan diameter (Ø)	Length (mm)
NVAF 31-2	3500	0.25	225	2850	380 - 415	350	400
NVAF 31-4	3750	0.37	400	2850	380 - 415	350	400
NVAF 31-6	3900	0.55	600	2850	380 - 415	350	400
NVAF 35-2	4000	0.37	225	2850	380 - 415	400	400
NVAF 35-4	4500	0.55	400	2850	380 - 415	400	400
NVAF 35-6	5000	0.75	600	2850	380 - 415	400	400
NVAF 40-2	5200	0.55	225	1460	380 - 415	450	450
NVAF 40-4	5800	0.75	400	1460	380 - 415	450	450
NVAF 40-6	6500	1.1	600	2850	380 - 415	450	450
NVAF 45-2	7000	0.75	225	1460	380 - 415	500	450
NVAF 45-4	8000	1.1	400	1460	380 - 415	500	450
NVAF 45-6	9000	1.5	600	2850	380 - 415	500	450
NVAF 50-2	11000	1.1	225	1460	380 - 415	550	500
NVAF 50-4	13000	1.5	400	1460	380 - 415	550	500
NVAF 50-6	15000	2.2	600	2850	380 - 415	550	500
NVAF 56-2	16000	1.5	225	1460	380 - 415	600	500
NVAF 56-4	18000	2.2	400	1460	380 - 415	600	500
NVAF 56-6	20000	3	600	2800	380 - 415	600	500
NVAF 63-2	21000	2.2	225	1460	380 - 415	670	550
NVAF 63-4	23000	3	400	1460	380 - 415	670	550
NVAF 63-6	25000	4	600	1460	380 - 415	670	550
NVAF 71-2	26000	3	225	1460	380 - 415	750	650
NVAF 71-4	28000	4	400	1460	380 - 415	750	650
NVAF 71-6	30000	5.5	600	1460	380 - 415	750	650
NVAF 80-2	31000	4	225	1460	380 - 415	850	650
NVAF 80-4	33000	5.5	400	1460	380 - 415	850	650
NVAF 80-6	35000	7.5	600	1460	380 - 415	850	650
NVAF 90-2	40000	5.5	225	1460	380 - 415	950	750
NVAF 90-4	45000	7.5	400	1460	380 - 415	950	750
NVAF 90-6	50000	11	600	1460	380 - 415	950	750
NVAF 100-2	55000	7.5	225	1460	380 - 415	1050	750
NVAF 100-4	65000	11	400	1460	380 - 415	1050	750
NVAF 100-6	75000	15	600	1460	380 - 415	1050	750
NVAF 112-2	77000	11	225	1460	380 - 415	1160	850
NVAF 112-4	80000	15	400	1460	380 - 415	1160	850
NVAF 112-6	90000	22	600	1460	380 - 415	1160	850
NVAF 125-2	95000	15	225	1460	380 - 415	1300	850
NVAF 125-4	115000	22	400	1460	380 - 415	1300	850
NVAF 125-6	125000	30	600	1460	380 - 415	1300	850